

PRIMEX[™]

Jotex Primex - Priming Coat

DESCRIPTION

JOTEX PRIMEX is a Premium Quality priming coat, with acrylic base and calibrated additives for giving a superior quality adhesion of the product with the substrate. It is also continuous protective coating on the surface. It seals the porosity in substrate if any. In addition to the above these also help in reducing the consumption of the coatings by reducing absorption of subsequent finish coats.

PROPERTIES

Test Name	Properties
Volume solid ratio	50 - 60%
VOC contents	Low VOC
DFT	25 - 30 micron/ coat
Density	1.40 +/- 0.05 kg/l
pH	8 - 10 units
Drying Time	30 Minutes Max.
Recoating Time	Minimum 4 Hours
Thinning	50% of potable water
Disposal	Dried material can be disposed in Municipal

RECOMMENDED APPLICATION AREAS

Concrete surface, cement plaster wall, gypsum board sheets and putty surfaces, etc.

METHOD OF APPLICATION

PREPARATION

- The temperature of the substrate should be min. 10°C and min. 3°C above the dew point of the air, temperature and relative humidity measured in the vicinity of the substrate.

SURFACE PREPARATION

- The substrate must be sound, clean, dry, free from dust, oil, grease and laitance etc. All traces of release agents must be removed. On chalky and dusty surfaces, all loose material must be removed by stiff bristle brushing.

HANDLING

Handle with care. Stir well before use.

APPLICATION

- Spray-Recommended
- Roller- Recommended
- Brush- Recommended

Typical paint application system

- Primer- Primex 1 coat
- Paint- Polycryl/Acristrech 2 coat

FEATURES AND BENEFITS

ADVANTAGES

- Acrylic emulsion Primer
- Excellent hiding
- High spreadibility
- Low VOC
- Easy Application

COVERAGE - 20 Ltr Bucket

1700 - 1800 sq.ft/bkt for single coat

SETTING AND CURING

The products set initially by Dry-curing in approximately 3 to 4 hours and the next activity can be taken up after 72 hours of application

PRIMEX[™]

Jotex Primex - Priming Coat

PACKAGING & STORAGE CONDITIONS

Std. Packing is 1Ltr., 4 Ltr., 20 Ltr. Buckets
Storage conditions are to keep the containers in a dry, cool, well ventilated space and away from source of heat and ignition. Containers must be kept tightly closed.

HEALTH & SAFETY

Use under well ventilated conditions. Do not breathe or inhale mist. Avoid skin contact. Eyes should be well flushed with water and medical attention sought immediately For detailed information on the health and safety hazards and precautions for use of this product, we refer to the Material Safety Data Sheet.

POT LIFE & SHELF LIFE

- In open pot 6 to 8 hours in shade (not under direct sunlight)
- 365 days from the date of manufacturing in standard storage warehouse.

TOOLS



Colour: White Only



WallingCO Products India LLP

Office 001, Lotus Plaza B, Opp. Karishma Society, Kothrud,
Pune - 411038, Maharashtra, India.

Tel.: + 91 95525 80896 / 97.

Email: order@wallingco.com